

# **SPEC SHEET**

## KoolMore 72 In. Commercial Back Bar Cooler in Black With Side Condenser and LED Lighting, 18 Cu. Ft

Model: KM-BC-3GD-SCBK

### **FEATURES**

- Spacious 18.3 Cu. Ft. Capacity: Holds up to 570 standard 12 oz. cans, ideal for bars, restaurants, and catering.
- Tempered Low-E Glass Doors: Three swing-style doors with insulation and clear visibility, energyefficient.
- Efficient Cooling Performance: Maintains 32°F to 50°F with eco-friendly refrigerant, operates up to 100°F ambient.
- Customizable Storage Solutions: Six adjustable metal shelves (64 lbs each) for flexible organization.
- Bright LED Interior Lighting: 6000K-7000K white LEDs at the top for enhanced visibility.
- Durable Construction: Aluminum interior, precoated steel, and stainless-steel exterior for longevity.
- User-Friendly Digital Controls: Digital thermostat for precise temperature adjustments.
- Narrow Design with Side-Mounted Compressor: 24-inch depth, space-saving with effective cooling.
- ETL Certified & Warranty: Meets ETL standards, 1-year parts and labor warranty.







#### **CLOSE UP IMAGES**











# TECHNICAL SPECS

### **Dimensions**

DIIIICIISIUIIS	
Height	34.2
Width	25
Length	72.8
Interior Height	29.17
Interior Width	55.75
Interior Depth	19.96
Depth Less Door	21.98
Depth With Door Open 90 Degrees	39.85
Depth Including Handles	25
Depth Excluding Handles	24
Minimum Back Air Clearance In	4 in.
Minimum Side Air Clearance In	4 in.
Weight lbs	203
Power Cord Length	97.5
Capacity	
Gross Cubic Feet	18.3
Net Cubic Feet	17.5
Individual Shelf Capacity	63.8 lbs
Features & Materals	
Color Finish	Black
Color Door Handles	Black
Defrost Type	Automatic
Refrigerant Type	R-600a
Door Style	Swing
Number Of Doors	3
Compressor Location	Bottom Right
Temperature Range	32-50 F
Ambient Temperature Range	100 F
Exterior Material	Precoated Sheet and Stainless-Steel
Interior Material	Aluminum
Door Material	Aluminum
Shelf Material Type	Metal
Interior Lights	LED
Interior Lights Color	White
Control Type	Digital
<b>Electric &amp; Certifications</b>	

Horsepower	0.16
Noise	65 dB
Amps	2.6
Hertz	60
Phase	1
Voltage	115
Wattage	290
Plug Type	NEMA 5-15P
Certifications	ETL Listed for Safety and Sanitation

### **Plan View**









